



2900 Commonwealth Ave. NE
Warren, OH 44483
800-FX-STRUT (800-397-8788)
Fax: 330-372-3666
Info@FlexStrut.com

FS-7270 & FS-7370 SERIES CONCRETE INSERT **DESIGN LOADS**

<u>PART NUMBER</u>	<u>INSERT LENGTH</u>	<u>ALLOWABLE LOAD</u>
FS-7250 & FS-7350	4"	800 LB
FS-7251 & FS-7351	6"	1000 LB
FS-7252 & FS-7352	8"	1200 LB
FS-7253 & FS-7353	12"	2000 LB
FS-7254/70 & FS-7354/70	16" thru 20'	2000 LB/FT

- *Allowable loads based on a safety factor = 3.0 on ultimate capacity in 3,000 psi min. NWT concrete
- *Minimum required spacing between point loads = 12"
- *All connections require the use of 1/2" thru 3/4" strut nuts placed at a minimum of 2" from end of insert.
- *Recommended bolt torques as follows: 1/2"=50 ft-lb; 5/8" & 3/4"=100 ft-lb (3/8" thick anchor recommended)
- *Minimum required edge distance from centerline to concrete edge = 3" in both directions
- *Minimum required end distance from end of channel to concrete edge = 3" in both directions
- *For loads placed less than 2" from the end of the channel reduce the allowable load by 50%.
- *Allowable point load is reduced to 1,100 lb with 3/8" strut nuts.